

Amendments to the Claims

The following listing of claims replaces all prior listings, and all prior versions, of claims in the application.

Listing of Claims

1. (currently amended) An arrangement for the ascent and/or descent of one or a plurality of persons on an object, ~~characterized by comprising~~ at least one longitudinally extended rail-like profile (1, 1', 1'') having at least one guide component (41, 43, 103, 105, 204, 206, 208, 210, 253, 255) extending along the profile and a component for the accommodation of force transmission (9, 11, 42, 44, 109) onto the profile and/or guide component, and by a climbing aid having at least one climbing console (13, 15) having at least one platform or seat (25, 27) as well as a personal safety device and/or a handle (21, 23), as well as at least one force-transmitting element (17, 19, 45, 47, 117, 119, 217, 219, 261, 263) engaging in or on the force-transmitting component and/or profile and/or a drive (113, 123, 302, 306), as well as a device (22, 24, 71, 72, 73, 141, 143) holding the element or drive in or on the at least one guide component and/or profile.

2. (currently amended) The arrangement according to Claim 1, ~~characterized in that~~ wherein the at least one guide component and/or the force-transmitting component is formed by at least one rack-like or grid-like longitudinal guide.

3. (currently amended) The arrangement according to ~~one of Claims 1 or 2, characterized in that~~ Claim 1, wherein the climbing aid has at least one climbing console (13, 15), ~~preferably two,~~ having at least one force-transmitting element and/or drive, as well as at least one holding device for holding the force-transmitting element or drive in or on the guide component and/or force-transmitting component.

4. (currently amended) The arrangement according to ~~one of Claims 1 to 3, characterized in that~~ Claim 1, wherein the at least one rotating force-transmitting element engaging in or on the longitudinal guide component(s) and/or the force-transmitting component is a pinion.

5. (currently amended) The arrangement according to ~~one of Claims 1 to 4, characterized in that~~ Claim 1, wherein the climbing console is longitudinally extended with a handle arranged at the top end in the direction of ascent and a platform arranged at the downward end.

6. (currently amended) The arrangement according to ~~one of Claims 1 to 5, characterized in that~~ Claim 1, wherein the force-transmitting element engaging in or on the at least one guide component and/or force-transmitting component or the drive is blockable at least in the downward direction and ~~preferably~~ remains free to rotate or slide in the direction of ascent.

7. (currently amended) The arrangement according to ~~one of Claims 1 to 6, characterized in that~~ Claim 1, wherein the element engaging in or on the

at least one guide component and/or force-transmitting component or the drive is damped and/or operatively connected to another suitable motion-damping or motion-inhibiting means, such as an eddy-current brake, centrifugal brake, or linear brake system, that is, that free mobility of the respective climbing console is not possible in the downward direction or the direction downward.

8. (currently amended) The arrangement according to ~~one of Claims 1 to 7~~, characterized in that Claim 1, further comprising means for releasing brakes (61, 63) ~~are~~ arranged in the region of the handles for the actuation of the downward unblocking of the force-transmitting element or drive, in order to make possible a damped downward motion of the climbing console or climbing consoles with simultaneous activation of the rotation or damping elements.

9. (currently amended) The arrangement according to ~~one of Claims 1 to 8~~, characterized in that Claim 1, further comprising a retaining apparatus, ~~such as for example in the form of a safety belt or harness (85), is~~ arranged on at least one of ~~the~~ at least two climbing consoles for securing the person using the climbing aid.

10. (currently amended) The arrangement according to ~~one of Claims 1 to 9~~, characterized in that Claim 1, wherein the longitudinally extended rail-like profile is fastenable to an object or loosely mobile.

11. (currently amended) The arrangement according to ~~one of Claims 1 to 10, characterized in that~~ Claim 1, wherein at least one force-transmitting element is both blockable with brakes and also rotationally or linearly damped.

12. (currently amended) The arrangement according to ~~one of Claims 1 to 11, characterized in that~~ Claim 1, wherein along the longitudinally extended profile and at least approximately transversely to the longitudinal extension of the profile there are arranged retaining bars provided, ~~for example, for the suspension of auxiliary ladders.~~

13. (currently amended) The arrangement according to ~~one of Claims 1 to 12, characterized in that~~ Claim 1, wherein the force-transmitting elements are provided with a drive, ~~such as for example selected from the group consisting of~~ an electric motor, an internal combustion engine, and a linear motor, etc.

14. (currently amended) The arrangement according to ~~one of Claims 1 to 13, characterized in that~~ Claim 1, wherein the force-transmitting elements are each connected to a drive motor, via gears ~~as appropriate, in such fashion that each drive motor is provided in order to drive preferably drives~~ at least the dead weight of the climbing console ~~in question or of the arrangement as a whole~~ upward upon activation.

15. (currently amended) The arrangement according to ~~one of Claims 13 or 14, characterized in that~~ Claim 14, wherein the drive motor is actuatably

operatively connected to the platform, the seat, and/or the handle so that the drive motor can be activated or deactivated ~~for example by~~ unloading the platform or seat or by actuation of the handle or by electronic control.

16. (currently amended) The arrangement according to ~~one of Claims 13 to 15, characterized in that~~ Claim 14, wherein the drive motor is additionally equipped as a generator in order to recover current during downward movement of the arrangement in order to feed for example a battery or rechargeable battery pack or a so-called Supercap (SCAP).

17. (currently amended) A method for the ascent and/or descent of a person on an object using an arrangement ~~according to one of Claims 1 to 16, characterized in that~~ comprising at least one longitudinally extended rail-like profile (1, 1', 1'') having at least one guide component (41, 43, 103, 105, 204, 206, 208, 210, 253, 255) extending along the profile and a component for the accommodation of force transmission (9, 11, 42, 44, 109) onto the profile and/or guide component, and by a climbing aid having at least one climbing console (13, 15) having at least one platform or seat (25, 27) as well as a personal safety device and/or a handle (21, 23), as well as at least one force-transmitting element (17, 19, 45, 47, 117, 119, 217, 219, 261, 263) engaging in or on the force-transmitting component and/or profile and/or a drive (113, 123, 302, 306), as well as a device (22, 24, 71, 72, 73, 141, 143) holding the element or drive in or on the at least one guide component and/or profile, wherein in said method the person can ascend ascends and/or descend descends along a longitudinally extended rail-like profile

on the object using a climbing aid in such fashion that the climbing aid is provided with force-transmitting elements engaging in or on the rail-like profile and/or a drive, the person ~~being able to unblock~~ unblocking the force-transmitting elements or drive while descending, and descent taking place in damped fashion by connecting the force-transmitting elements or the drive to one of a rotary dashpot, an eddy current brake, centrifugal brake, and a linear motor ~~or the like~~.

18. (currently amended) The method according to Claim 17, ~~characterized in that~~ wherein the climbing aid is fashioned in two parts and the person using the climbing aid first ascends using one console by rendering the force-transmitting elements or the drive free in the climbing direction while blocking the force-transmitting elements on the other console in order to prevent downward sliding of the other console; and that, after negotiating a certain climbing height, the person ascends with the other console by blocking the force-transmitting elements or the drive on the one console.

19. (currently amended) The method according to ~~one of Claims 17 or 18, characterized in that for~~ Claim 17, further comprising, in the descent of a the person using the climbing aid, the blocking of the force-transmitting elements or drive is unblocked and descent takes place in controlled or damped fashion.

20. (currently amended) A method for the ascent and/or descent of a person on an object using an arrangement ~~according to one of Claims 1 to 16,~~ characterized in that comprising at least one longitudinally extended rail-like profile (1, 1', 1'') having at least one guide component (41, 43, 103, 105, 204, 206, 208, 210, 253, 255) extending along the profile and a component for the accommodation of force transmission (9, 11, 42, 44, 109) onto the profile and/or guide component, and by a climbing aid having at least one climbing console (13, 15) having at least one platform or seat (25, 27) as well as a personal safety device and/or a handle (21, 23), as well as at least one force-transmitting element (17, 19, 45, 47, 117, 119, 217, 219, 261, 263) engaging in or on the force-transmitting component and/or profile and/or a drive (113, 123, 302, 306), as well as a device (22, 24, 71, 72, 73, 141, 143) holding the element or drive in or on the at least one guide component and/or profile, wherein in said method the person ~~can ascend~~ ascends and/or ~~descend~~ descends along a longitudinally extended rail-like profile on the object using a climbing aid in such fashion that by actuating a drive motor on either of the two consoles of the climbing aid, this drive motor drives at least the dead weight of the respective climbing aid negotiatingly upward, actuation ~~being able to take~~ taking place either automatically by unloading of the respective platform or seat or, ~~however,~~ by actuation of a corresponding control on the respective handle, and that after the negotiation of a certain climbing height, the drive motor is deactivated and the drive motor on the other climbing aid is activated, ~~for example~~ automatically, in order to drive the other climbing aid correspondingly upward.

21. (currently amended) The method according to Claim 20, ~~characterized in that~~ wherein the drive motors are activated or deactivated automatically in that, ~~for example~~ on unloading of the platform or seat, the respective drive motor, ~~such as for example a battery-driven electric motor,~~ is activated while the other drive motor remains deactivated automatically by loading of the platform or seat or under electronic control.

22. (currently amended) The method according to ~~one of Claims 20 or 21,~~ characterized in that Claim 20, wherein in the descent of a person using the arrangement ~~according to the invention,~~ the drive motors are operated in the manner of generators for generating current and ~~for example a battery,~~ such as for example feeding the current to a rechargeable battery pack for operating the drive motors ~~or a Supercap (CAP), can be fed with the current generated.~~

23. (currently amended) The method according to Claim 20, wherein ~~the object is one of a use of the arrangement according to one of Claims 1 to 16 for the climbing of~~ high-voltage pole, cableway mast, silo, building wall, and shaft wall ~~poles, cableway masts, silos, building walls, shaft walls, etc.~~

24. (currently amended) The ~~use of~~ method according to Claim 20, ~~including using~~ the arrangement ~~according to one of Claims 1 to 16 as a~~ rescue device or as a fire ladder, said object being a tall building ~~in the case of tall buildings.~~

25. (currently amended) ~~The use of method according to Claim 20, including using the arrangement according to one of Claims 1 to 16 as a self-contained person lift.~~

26. (currently amended) A rail-like profile (1, 1', 1'') for an arrangement ~~according to one of Claims 1 to 16~~ for the ascent and/or descent of one or a plurality of persons on an object, characterized by the rail-like profile comprising at least one guide component (41, 43, 103, 105, 204, 206, 208, 210, 253, 255) extending along the profile as well as a component (9, 11, 42, 44, 109) for accepting force transmission onto the profile and/or guide component.

27. (currently amended) The rail-like profile according to Claim 26, ~~characterized in that wherein~~ the at least one guide component and/or the force-transmitting component is formed by at least one rack-like or grid-like longitudinal guide.

28. (currently amended) ~~The use of~~ A method of using a rail-like profile for an arrangement for the ascent and/or descent of one or a plurality of persons on an object, the rail-like profile comprising at least one guide component (41, 43, 103, 105, 204, 206, 208, 210, 253, 255) extending along the profile as well as a component (9, 11, 42, 44, 109) for accepting force transmission onto the profile and/or guide component, said method comprising using the rail-like profile according to one of Claims 26 or 27 as guide for a climbing aid on an outer façade of one of a high-rise building, on a

high-voltage pole, ~~on a cableway mast, on silos, on shaft walls, etc~~ a silo, and a shaft wall.

29. (currently amended) ~~The use of~~ A method of using a rail-like profile for an arrangement for the ascent and/or descent of one or a plurality of persons on an object, the rail-like profile comprising at least one guide component (41, 43, 103, 105, 204, 206, 208, 210, 253, 255) extending along the profile as well as a component (9, 11, 42, 44, 109) for accepting force transmission onto the profile and/or guide component, said method comprising using the rail-like profile according to one of Claims 26 or 27 for the guidance of a rescue devices ~~device~~ on a tall ~~buildings~~ building.